


KRAMPE HAREX®

KNOW WHY.

Data Sheet | Fibres


Version 05/2019

WIRE FIBRE HOOKED ENDS

① Type of fibre ③ Length ⑤ Material Specification

DE 50/0,75 N

② Shape of fibre ④ Diameter



GEOMETRY

① Type of fibre	wire fibre
② Shape of fibre	hooked ends
③ Length (L)	50 mm ± 10%
④ Diameter (d)	0,75 mm ± 10%
Cross section	round
Ratio (L/d)	67

FIBRE NETWORK

Quantity of fibres	5.770 fibres/kg
Minimum dosage	15 kg/m ³

MATERIAL PROPERTIES

⑤ Material specifications	Normal tensile strength
Material	Steel
Material number	1.0313
Tensile strength	1.200 N/mm ²
Modulus of elasticity	210.000 N/mm ²

CERTIFICATIONS & SYSTEM APPROVALS

Standards (DIN)	EN 14889-1
Certifications (DIN)	EN ISO 9001:2015, EN ISO 50001



Subject to change without notice. All specifications are only a general description of our products. For detailed information please ask for our product leaflets.

INFO

Krampe Harex® Fibres are a cost effective solution to conventional reinforcement methods.:

- > **Industrial floors**
- > **Tunneling applications**
- > **Precast concrete elements**
- > **Applications in residential buildings**

In relation to our **Service+** offer, we determine the suitable type of fibre, the optimal dosage and the necessary concrete strength. Further information can be found on our website krampeharex.com.

PACKAGING


Bags

Boxes*

Big Bag

STORAGE


Keep Dry

* Fibres are magnetically linearized.